SIEMENS

Data sheet 6GT2803-0BM00

Product type designation

Charging station for handheld unit

SIMATIC RF300 Handheld Charging/docking station Charging station for SIMATIC RF350M incl. wide-range power supply unit



Type of current supply	wide-range power supply including charging station for RF350M
Suitability for use	loading of accumulators for RF350M and for communication to a PC via USB and Ethernet
Suitability for operation	for RF350M

Electrical data / Input	
Supply voltage / Rated value	230 V
Supply voltage / rated value	100 240 V
Type of voltage / of the supply voltage	AC
Line frequency	
● 50 Hz	Yes
• 60 Hz	Yes

Electrical data / Output	
Voltage curve / at output	DC
Output voltage / at DC / Rated value	24 V
Output current	
Rated value	1.25 A

Interfaces

Number of electrical connections	
• for power supply	1
Type of electrical connection	
• at input	Euro plug with 1.8 m connecting cable
• at output	Low Voltage connector (female, 2 pin, 5.5 mm)

Standards, specifications, approvals

Standard

• for safety / from CSA and UL

cULus listed 41TJ, E209833

Further information / Internet-Links

Internet-Link

• to website: Selector SIMATIC NET SELECTION TOOL

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx Download Manager

• to website: Industry Online Support

https://support.industry.siemens.com/cs/ww/en/view/67384964

http://www.siemens.com/ident/rfid

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

last modified: 05/08/2020