

### Product type designation

### RF240R reader

SIMATIC RF200 Reader RF240R; RS422 interface (3964R); IP67, -25 to +70 °C; 50x 50x 30 mm; with integrated antenna



Suitability for operation	ISO 15693 Transponder (MDS Dxxx), for connecting to communication modules
<b>Radio frequencies</b>	
Operating frequency / Rated value	13.56 MHz
Range / maximum	65 mm; Range is dependent on transponder type: observe <a href="http://support.automation.siemens.com/WW/view/en/67384964">http://support.automation.siemens.com/WW/view/en/67384964</a>
Protocol / with radio transmission	ISO 15693, ISO 18000-3
Transfer rate / with radio transmission / maximum	26.5 kbit/s
Product feature / multitag-capable	No
<b>Electrical data</b>	
Transfer rate / at the point-to-point connection / serial / maximum	115.2 kbit/s
Transmission time / for user data	
• for write access / per byte / typical	0.6 ms
• for read access / per byte / typical	0.6 ms
<b>Interfaces</b>	
Standard for interfaces / for communication	RS422
Type of electrical connection	M12, 8-pin

Mechanical data	
Material	PA6.6
Color	anthracite
Tightening torque / of the screw for securing the equipment / maximum	1.5 N·m
Mounting distance / relating to metal surfaces / recommended / minimum	0 mm

Supply voltage, current consumption, power loss	
Supply voltage	
<ul style="list-style-type: none"> <li>• at DC / Rated value</li> </ul>	24 V
<ul style="list-style-type: none"> <li>• at DC</li> </ul>	20.4 ... 28.8 V
Consumed current / at DC / at 24 V	
<ul style="list-style-type: none"> <li>• typical</li> </ul>	0.05 A

Ambient conditions	
Ambient temperature	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-20 ... +70 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-25 ... +80 °C
<ul style="list-style-type: none"> <li>• during transport</li> </ul>	-25 ... +80 °C
Protection class IP	IP67
Shock resistance	EN 60721-3-7 Class 7 M2
Shock acceleration	500 m/s <sup>2</sup>
Vibrational acceleration	200 m/s <sup>2</sup>

Design, dimensions and weights	
Width	50 mm
Height	30 mm
Depth	50 mm
Net weight	0.06 kg
Mounting type	2 x M5 screws
Wire length	
<ul style="list-style-type: none"> <li>• for RS 422 interface / maximum</li> </ul>	1000 m

Product features, product functions, product components / general	
Display version	3-color LED
Product feature / silicon-free	Yes

Standards, specifications, approvals	
Certificate of suitability	Radio according to R&TTE guidelines EN300 330 and EN 301489, FCC, cULus
Certificate of suitability	
<ul style="list-style-type: none"> <li>• IECEx</li> </ul>	No
MTBF	430 y

#### Further information / Internet-Links

Internet-Link

- to website: Selector SIMATIC NET SELECTION TOOL
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/67384964>

<http://www.siemens.com/ident/rfid>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

**last modified:**

05/12/2020