

Product type designation

Product description

MM FO Robust Cable GP

Glass fiber-optic cable, preferred length, preassembled
FO Robust Cable GP 50/125, pre-assembled with 2x LC Duplex
connectors, Length 100 m



Suitability for use	Waterproof cable (lengthwise and sideways) with non-metallic protection against rodents for use indoors and outdoors as well as for direct routing underground
Version of the assembled FO cable	Pre-assembled with 2x LC DUPLEX connectors
Cable designation	AT-V(ZN)H(ZN)BH 2G50/125 OM2+
Wire length	100 m

Optical data	
Damping ratio per length	
<ul style="list-style-type: none"> at 850 nm / maximum 	2.7 dB/km
<ul style="list-style-type: none"> at 1300 nm / maximum 	1 dB/km
Bandwidth length product	
<ul style="list-style-type: none"> at 850 nm 	600 GHz·m
<ul style="list-style-type: none"> at 1300 nm 	1200 GHz·m

Mechanical data	
Number of fibers / per FOC core	1
Number of FO cores / per FOC cable	2
Version of the FO conductor fiber	Multi-mode gradient fiber 50/125/245 µm, OM2

Design of the FOC core	Solid core, diameter 900 µm
Design of the fiber-optic cable	segmentable
Outer diameter <ul style="list-style-type: none"> • of the optical fibers • of the optical fiber sheath • of the FOC core sheath 	50 µm 125 µm 2.2 mm
Outer diameter / of the cable	7.5 mm
Material <ul style="list-style-type: none"> • of the fiber-optic cable core • of the optical fiber sheath • of the FOC core sheath • of the fiber-optic cable sheath • of the strain relief 	Quartz glass Quartz glass PE flame retardant PE flame retardant Aramid fibers and glass roving
Color <ul style="list-style-type: none"> • of the FOC core sheath • of cable sheath 	orange/black, with direction arrow Black
Bending radius <ul style="list-style-type: none"> • with single bend / minimum permissible • with multiple bends / minimum permissible 	25 mm 40 mm
Tensile load <ul style="list-style-type: none"> • during installation / short-term • during operation / maximum 	2000 N 1000 N
Short-term shear force per length	600 N/cm
Continuous lateral force per length	200 N/cm
Weight per length	67 kg/km

Ambient conditions

Ambient temperature <ul style="list-style-type: none"> • during operation • during storage • during transport • during installation 	-40 ... +70 °C -40 ... +70 °C -40 ... +70 °C -20 ... +60 °C
Burning behavior	flame-resistant acc. to IEC 60332-3-24
Chemical resistance <ul style="list-style-type: none"> • to mineral oil • to grease • to water 	conditional resistance conditional resistance resistant
Radiological resistance / to UV radiation	resistant

Product features, product functions, product components / general

Product feature <ul style="list-style-type: none"> • halogen-free • silicon-free 	Yes Yes
--	------------

Product component / Rodent protection	Yes
Wire length	
<ul style="list-style-type: none"> • for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum 	5000 m
<ul style="list-style-type: none"> • for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum 	750 m
<ul style="list-style-type: none"> • for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum 	2000 m
<ul style="list-style-type: none"> • for glass FOC / with 10GBaseSR / for Industrial Ethernet / maximum 	60 m
<ul style="list-style-type: none"> • for glass FOC / with PROFIBUS / maximum 	3000 m

Standards, specifications, approvals

Certificate of suitability	
<ul style="list-style-type: none"> • RoHS conformity 	Yes

Further information / Internet-Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAx Download Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com

last modified: 06/24/2020