







PRICE LIST

Tel. 22028444 – Fax 2202844

Panel Lamps, Push Buttons, Switches, Meters, Isolators, Ferrules, Klemmes, Relays, MCB, RCD, Surge Arrestors

1. Water Level Float Switch

TYPE	CHARACTERISTICS	PRICE	PHOTO
CAY-1	2 m cable wire (0.75mm ²)	5.40	
	5 m cable wire (0.75mm ²)	8.88	
CAY-2	2 m cable wire (0.75mm ²)	5.40	
	5 m cable wire (0.75mm ²)	8.88	
CAY-3	2 m cable wire (0.75mm ²)	6.00	
	5 m cable wire (0.75mm ²)	9.46	
CAY-4	2 m cable wire (0.75mm ²)	6.00	
	5 m cable wire (0.75mm ²)	9.46	

Technical Parameters for the float switch

- Microswitch: 10(8)A 250V~10(4)A 380V
- Switch currency: +++ ≥ 50 000switch workings tested by VDE specialization
- Protective connection: T 70U
- Protection: Waterproof
- Max. Temperature: 70° C
- Working pressure: Max. 1bar
- Circuit breaking capacity: Directly KW with 250V
- Standard Cable Length: 5m ~ 100mm or According to customer's request
- Float: Polypropylene
- Cable: Polypropylene Jacket
- Counter Weight: Polypropylene Sealed Housing
- Cable Material: HO7RN- F3x0.75mm², PVC (3x0.5mm², 3x0.75mm², 3x1.0mm²)

Rated Voltage	AC 125-250V
Max. Current	AC 16(4)A
Frequency	50/60Hz
Max. Using Temperature	50
Protection Degree	IP68