# IME08-03BPSZW2S

**INDUCTIVE PROXIMITY SENSORS** 



# IME08-03BPSZW2S | IME

INDUCTIVE PROXIMITY SENSORS



## Ordering information

| Туре            | Part no. |
|-----------------|----------|
| IME08-03BPSZW2S | 1074042  |

Included in delivery: BEF-MU-M08 (1)

Other models and accessories → www.sick.com/IME

Illustration may differ



## Detailed technical data

#### Features

| Housing                           | Cylindrical thread design |
|-----------------------------------|---------------------------|
| Housing                           | Standard                  |
| Thread size                       | M8 x 1                    |
| Diameter                          | Ø 8 mm                    |
| Sensing range S <sub>n</sub>      | 3 mm                      |
| Safe sensing range S <sub>a</sub> | 2.43 mm                   |
| Installation type                 | Quasi-flush               |
| Switching frequency               | 1,000 Hz                  |
| Connection type                   | Cable, 3-wire, 2 m        |
| Switching output                  | PNP                       |
| Output function                   | NO                        |
| Electrical wiring                 | DC 3-wire                 |
| Enclosure rating                  | IP67 <sup>1)</sup>        |
| Special features                  | Triple sensing range      |

<sup>1)</sup> According to EN 60529.

#### Mechanics/electronics

| Supply voltage                 | 10 V DC 30 V DC  |
|--------------------------------|------------------|
| Ripple                         | ≤ 10 %           |
| Voltage drop                   | $\leq 2 V^{(1)}$ |
| Time delay before availability | ≤ 50 ms          |

 $^{1)}$  At I<sub>a</sub> max.

<sup>2)</sup> Ub and Ta constant.

<sup>3)</sup> Of Sr.

# IME08-03BPSZW2S | IME

INDUCTIVE PROXIMITY SENSORS

| Hysteresis                             | 1 % 15 %                                |
|--|---|
|  |   |
| Reproducibility                        | $\leq 5 \%^{2) 3}$                      |
| Temperature drift (of S <sub>r</sub> ) | ± 10 %                                  |
| EMC                                    | According to EN 60947-5-2               |
| Continuous current I <sub>a</sub>      | ≤ 200 mA                                |
| Current consumption, no load           | ≤ 10 mA                                 |
| Cable material                         | PVC                                     |
| Conductor size                         | 0.25 mm <sup>2</sup>                    |
| Cable diameter                         | Ø 3.9 mm                                |
| Short-circuit protection               | ✓                                       |
| Reverse polarity protection            | ✓                                       |
| Power-up pulse protection              | ✓                                       |
| Shock and vibration resistance         | 30 g, 11 ms/10 Hz 55 Hz, 1 mm           |
| Ambient operating temperature          | -25 °C +75 °C                           |
| Ambient temperature, storage           | -25 °C +75 °C                           |
| Housing material                       | Brass, nickel-plated                    |
| Sensing face material                  | Plastic, PA 66                          |
| Housing length                         | 52 mm                                   |
| Thread length                          | 34 mm                                   |
| Tightening torque, max.                | ≤ 5 Nm                                  |
| Items supplied                         | Mounting nut, brass, nickel-plated (2x) |
| UL File No.                            | NRKH.E181493                            |

<sup>1)</sup> At I<sub>a</sub> max.

<sup>2)</sup> Ub and Ta constant.

<sup>3)</sup> Of Sr.

## Safety-related parameters

| MTTFD                      | 1,735 years                                    |
|----------------------------|--|
| DC <sub>avg</sub>          | 0 %  |
| Reduction factors          |  |
| Note                       | The values are reference values which may vary |
| St37 steel (Fe)            | 1  |
| Stainless steel (V2A, 304) | Approx. 0.75                                   |
| Aluminum (Al)              | Approx. 0.46                                   |
| Copper (Cu)                | Approx. 0.42                                   |
| Brass (Br)                 | Approx. 0.56                                   |
| Installation note          |  |
| Remark                     | Associated graphic see "Installation"          |
| A                          | 3 mm   |
| В                          | 20 mm  |
| c                          | 8 mm   |
| D                          | 9 mm   |

# IME08-03BPSZW2S | IME

INDUCTIVE PROXIMITY SENSORS


| F | 1 mm  |
|---|-------|
| F | 30 mm |

Classifications

| ECI@ss 5.0     | 27270101 |
|----------------|----------|
| ECI@ss 5.1.4   | 27270101 |
| ECI@ss 6.0     | 27270101 |
| ECI@ss 6.2     | 27270101 |
| ECI@ss 7.0     | 27270101 |
| ECI@ss 8.0     | 27270101 |
| ECI@ss 8.1     | 27270101 |
| ECI@ss 9.0     | 27270101 |
| ECI@ss 10.0    | 27270101 |
| ECI@ss 11.0    | 27270101 |
| ETIM 5.0       | EC002714 |
| ETIM 6.0       | EC002714 |
| ETIM 7.0       | EC002714 |
| ETIM 8.0       | EC002714 |
| UNSPSC 16.0901 | 39122230 |

#### Installation note

Quasi-flush installation



## **Connection diagram**

Cd-001



INDUCTIVE PROXIMITY SENSORS

#### **Recommended accessories**

Other models and accessories -> www.sick.com/IME

|                                 | Brief description   | Туре        | Part no. |
|---------------------------------|---|-------------|----------|
| Mounting bra                    | ckets and plates  |             |          |
|                                 | Mounting plate for M8 sensors, steel, zinc coated, without mounting hardware  | BEF-WG-M08  | 5321722  |
|                                 | Mounting bracket for M8 sensors, steel, zinc coated, without mounting hardware  | BEF-WN-M08  | 5321721  |
| Terminal and alignment brackets |   |             |          |
|                                 | Clamping block for round sensors M8, without fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included | BEF-KH-M08  | 2051477  |
|                                 | Clamping block for round sensors M8, with fixed stop, plastic (PA12), glass-fiber reinforced, mounting hardware included    | BEF-KHF-M08 | 2051478  |

# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

